



Power supply

10-18 V DC

10-18 V DC

10-18 V DC

10-18 V DC

10-18 V DC

10-24 V DC

10-18 V DC

Network Connectivity

GSM/LTE

GSM/LTE

Ethernet

Ethernet

GPRS/LTE

GPRS/LTE

Ethernet or GPRS/LTE

SIM Card

1 x 4FF (Nano)

1 x 4FF (Nano)

-

-

1 x 4FF (Nano)

1 x 4FF (Nano)

2 x 4FF (Nano)

Communication channels

2

2

2

2

1

1

1

Backup channels

2

2

2

2

1

1

1

Remote Monitoring

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Remote Control

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Proteagus 2 App

Yes

Yes

Yes

Yes

Yes

Yes

Yes

SIA FSK Compatibility

-

-

-

-

-

Yes

Yes

Controllable Outputs/Inputs

3

3

3

3

2

2

2

Connection to Panel

Serial Bus

Landline Dialer
(TIP RING)

Serial Bus

Landline Dialer
(TIP RING)

Serial Bus,
Landline Dialer
(TIP RING)

Serial Bus,
Landline Dialer
(TIP RING)

Serial Bus,
Landline Dialer
(TIP RING)

Monitoring Protocols

TRK3,
DC-09_2007,
DC-09_2012,
TL150

TRK3,
DC-09_2007,
DC-09_2012,
TL150

TRK3,
DC-09_2007,
DC-09_2012,
TL150

TRK3,
DC-09_2007,
DC-09_2012,
TL150

TRK8,
DC-09_2007,
DC-09_2012,
TL150

TRK8,
DC-09_2007,
DC-09_2012,
TL150

TRK8,
DC-09_2007,
DC-09_2012,
TL150

Configuration

Proteagus 2 app,

-

TrikdisConfig
PC program
(remote/local)

USB Mini-B

Proteagus 2 app,

-

TrikdisConfig
PC program
(remote/local)

USB Mini-B

Proteagus 2 app,

-

TrikdisConfig
PC program
(remote/local)

USB Mini-B

Proteagus 2 app,

-

TrikdisConfig
PC program
(remote/local)

USB Mini-B

Proteagus 2 app,

Fast set-up
templates

TrikdisConfig
PC program
(remote/local)

USB-C

Proteagus 2 app,

Fast set-up
templates

TrikdisConfig
PC program
(remote/local)

USB-C

Proteagus 2 app,

Fast set-up
templates

TrikdisConfig
PC program
(remote/local)

USB-C