

FLEXi

SP3


Adaptable Security Panel

Wi-Fi
+4G

Wi-Fi
+2G

Wi-Fi
+Ethernet

Wi-Fi



Adaptability and Speed

Designed to combine the best features of TRIKDIS security control panels, communicators and controllers

Security Control Panel FLEXi SP3

FLEXi is a hybrid security control panel with on-board **WiFi** and **Cellular** or **Ethernet** connectivity. Unique feature set allows you to use this panel both in intrusion alarm and automation installations.



Old System Takeover

Replace any alarm panel without changing resistors in each sensor. In **TrikdisConfig** you can **set** what **resistor nominal** value is used with FLEXi. This saves a lot of time during a retro-fit installation.



Speed

Integrated **4G, WiFi** and Ethernet **allows to save precious seconds** in case of a break-in.

Fast connectivity also allows for **faster remote configuration and remote control**.




Cost Effective

Integrating the communicator into the alarm panel board allows to **save a lot in the final price**. WiFi allows to **save on cellular data** costs. Remote configuration allows to add users, change passwords and other settings without visiting the site.




Adaptability

FLEXi expandable up to **32 zones** and up to **16 OUTs**. Also add additional **VHF/UHF** band radio or **SigFox** channel and achieve reliable **multi-path** communication.



Modifications

Tailored to individual cases, different connection requirements, and **meets different user needs** so you will make a great solution every time.



FLEXi can be ordered with **2G or 4G** modems.

WiFi should be used **as the primary channel**. If it stops working, connection will switch automatically to cellular.



FLEXi makes it possible to use redundant Internet connection by connecting to networks of two independent communications providers: **the main — via WiFi, and the backup — via Ethernet**. If connection of one provider fails, the security panel will stay connected.



It is not **necessary to lay a IP cable for connection to the router**. The control panel is ready to operate straight out the box.




Wi-Fi



CELLULAR



VHF/UHF



ETHERNET



sigfox

Remote control

Offer your clients a **app** without investing in its development. This will increase the value and appeal of your company's security services.



Remote control and notifications via Protegus app

Optional notifications:





via SMS



via call



FLEXi can send multiple notifications: app push messages, SMS text messages and phone calls (working SIM card required).



FLEXi

SP3 control panel board

FLEXi SP3 control panel board

Wire for connecting battery

Resistor 2,2 k Ω

Plastic spacer (mounting parts)

Two antennas, cellular and Wi-Fi with 2,5 m long cables



FLEXi Kits

When it comes to new installations we have a decent approach to it. We prepared **FLEXi kits for fast and convenient installations**, all in one metal housing with carefully selected equipment for full FLEXi potential.



FLEXi SP3 control panel board, built into metal housing (200 x 210 x 80 mm)

Metal housing K02 with **Mean Well impulse power supply**

Resistor 2,2 k Ω

Two antennas, cellular and Wi-Fi with 2,5 m long cables

Wire for connecting battery

Has **tamper sensor**

Terminal block with **3,15 A fuse**



FLEXi SP3 control panel board, built into metal housing (285 x 280 x 80 mm)

Metal housing K01 with **40 VA transformer**

Resistor 2,2 k Ω


Two antennas, cellular and Wi-Fi with 2,5 m long cables

Wire for connecting battery

Has **tamper sensor**

Terminal block with **0,5 A fuse**

Compatible Keypads



SK232 LED W




CR16 / CR-LCD / KP- Touch Screen



P ▲ R ▲ D O X

**K636 / K10H(V) / K32 LED / K32+ LED / K35/
TM70 / TM 50**

Compatible Devices




Communicator T16

Add additional radio channel for most secure communication to Central Monitoring Station.



Module SF485

Add additional communication channel through SigFox radio network




Expander iO8

With iO-8 **FLEXi** obtains **32 zones** and **16 OUTs**


Make it Wireless

With RF-SH module **FLEXi** can easily connect to **Crow's wireless security sensors**



Shepherd series

SH-Sirint / SH-KP / SH-PIR / SH-MAG / SH-FLOOD / SH-CRT / SH-SMK / SH-GBD



Freewave2 series


FW2-Panic N / FW2-Remote N / FW2-GBD N / FW2-EDS3000AM N with Anti-Masking / FW2-Neo N / FW2-Mag N / FW2-Flood N / FW2-Curtain N / FW2-Smoke N



| | |
|--|--|
| Power supply | 16-24 V, 2,5 A AC |
| Current consumption | Up to 50 mA (stand-by), Up to 200 mA (short-term, while sending) |
| WiFi frequency, protocol, encryption | 2,4 GHz, 802.11 b/g/n, WPA, WPA2, WPA mixed |
| WiFi network configuration | DHCP or manual |
| SIM card | 1, NANO size |
| GSM/GPRS modem | Quad-band |
| 4G modem | 4G (LTE-FDD) with migration to 3G (WCDMA) and 2G (GSM/EDGE) feature |
| Ethernet port | RJ-45 connector |
| Event transmission directions | <ul style="list-style-type: none"> - To main and backup receivers of 2 different security companies; - iOS/Android Protegus mobiliąsias programas; - To 8 mobile phones via SMS messages. - Calls to 8 mobile phones. Vocal event notification |
| Event transmission channels | 2G or 4G, WiFi, LAN (with module E485), SMS, Voice call, VHF/ UHF radio (with transmitter T16) |
| Programmable communication channel/direction priority | Yes |
| Pranešimų šifravimas | TRK AES 128, SIA IP AES 128 / Contact ID codes |
| Internal clock | Yes |
| Events log memory | 1000 entries, oldest deleted automatically. |
| User codes | 40 |
| Duress code | Yes |
| No. of partitions | 8 |
| No. of zones | 10 (20 if set ATZ), expandable up to 32 with expanders |
| No. of PGM outputs | 2 (12 if IO terminals are set as OUT) Expandable to 16 with expanders |
| No. of keypads | 8 |
| No. of RFID readers | 2 (Wiegand 26/34) |
| No. of compatible temperature sensors | 8 |
| No. of compatible electronic (iButton) keys | 40 |
| Compatible wireless systems | Crow Shepherd, Freewave2 via extra add-on RF module |
| Operating environment | Temperature from -10 °C to +50 °C, relative humidity 80%, at +20 °C, no condensation. |

FLEXi

Adaptable Security Panel
SP3



Address: Draugystės st. 17, LT-51229 Kaunas, Lithuania
Tel. +370 37 408040
Email: info@trikdis.lt

www.trikdis.com